

TECHNICAL DATA SHEET FOR: LED Lighting Tower

John F Hunt
POWER

60% Less Fuel | 40% More Light | Generating 2000w of Light

- Engine: Kohler
- Alternator: Sincro
- Alternator Output 5kVa
- 4 stabilizing legs
- 7 mast sections
- 8 x 250w LED & 593, 600 Lumens
- Hydraulic Mast Erection
- 15 Second Mast raise/lower time
- Hydraulic system uses bio-degradable oil
- 358° Mast rotation
- 9m maximum mast height
- IP 65 Lamp Housing protection
- Standard road lights and reflectors
- IP23 Enclosure protection
- 125% Bunding
- 2 x 220v single phase 16A Power outlet sockets

Fuel Tank Capacity (litres)	Fuel Consumption (l/h)	Max Run Time (Hours)	Noise level @ 7 m dB(A)	Weight Un-Fuelled (kg)	Weight Fully Fuelled (kg)	Dimensions Fully Deployed (mm)	Transport Dimensions (mm)
140	1.05	150	59	1030	1138	L 2800 W 2450 H 9200	L 2450 W 1300 H 2300

South East Depot – Europa Park, London Road
Grays, Essex, RM20 4DB
T: 01375 366766 E:power@johnfhunt.co.uk

Midlands Depot – Fairfield Park, Off Fairfield Road,
Halesowen, West Midlands B62 9JL
T: 0121 559 1818 E:power@johnfhunt.co.uk

South West Depot – Bradley Road,
Bristol BS20 7NZ
T: 0117 901 2199 E:power@johnfhunt.co.uk

North East Depot – Station Lane, Birtley, Gateshead,
Tyne & Wear DH2 1AJ
T: 0191 4111 200 E:power@johnfhunt.co.uk



www.johnfhuntpower.co.uk