

TECHNICAL DATA SHEET FOR: 200kVA Silenced Generator

John F Hunt POWER

- HOT DIP GALVANISED SOUND ATTENUATED ENCLOSURE. AVERAGE 68 dB(A) @ 7 METERS.
- POWDER COATED GREY RAAL 7035.
- BUNDED 270 LITRE BASE FUEL TANK COMPLETE WITH 3 WAY VALVE.
- CENTRAL LIFT POINT AND FORKLIFT POCKETS COMPLETE WITH RUBBER BUMPERS.
- 4 POLE CIRCUIT BREAKER WITH EARTH LEAKAGE PROTECTION
- HARDWIRE VIA COPPER BUS BARS
- MICRO SWITCH PROTECTION MOUNTED UNDER PERSPEX
- CT FOR GENSET PARALLELING
- RACOR FILTER



- DEEP SEA 8610 LOADSHARE CONTROL PANEL
- PLASTIC COATED LOCKS/HANDLES. LOCKABLE CANOPY WITH SINGLE COMMON KEY
- IVECO WATER SEPARATOR FILTER
- SUMP OIL VAC PUMP
- BATTERY ISOLATOR
- SOCKET KIT – 1 X 125AMP 3 PHASE
- OIL PRESSURE & WATER TEMPERATURE SENSOR
- MOTORISED MCCB
- VELCB WITH ON/OFF SWITCH
- EXTERNAL CONTACT FOR AUTOSTART

ENGINE Ref:- IVECO / CUMMINS ALTERNATOR Ref:- MECC ALTE

| Standby kVA | Prime Power kVA. | Engine Make/Type | Governor | Tank Capacity Litres | Fuel (L/H) Consumption | | | dB(A) @ 7m | Size (mm) | Weight (Kg) | Control Panel |
|-------------|------------------|-------------------|------------|----------------------|------------------------|-------|-------|------------|----------------------------------|-------------|----------------------------|
| | | | | | 50% | 75% | 100% | | | | |
| 220 | 208 | IVECO/ CUMMINS | Electronic | 270 | 21.55 | 32.33 | 43.10 | 68 | L - 3380 W - 1130 H - 2000 | 2690 | Deep Sea 8610 Loadshare |

South East Depot – Europa Park, London Road
Grays, Essex, RM20 4DB
T: 01375 366766 E:power@johnfhunt.co.uk

Midlands Depot – Fairfield Park, Off Fairfield Road,
Halesowen, West Midlands B62 9JL
T: 0121 559 1818 E:power@johnfhunt.co.uk

South West Depot – Bradley Road,
Bristol, BS20 7NZ
T: 0117 901 2199 E:power@johnfhunt.co.uk

North East Depot – Station Lane, Birtley, Gateshead,
Tyne & Wear DH2 1AJ
T: 0191 4111 200 E:power@johnfhunt.co.uk

www.johnfhuntpower.co.uk