



200kVA

Silenced Generator

Engine Ref: IVECO / CUMMINS
ALTERNATOR Ref: MECC ALTE

- Hot dip galvanised sound attenuated enclosure
- Average 68 dBA @ 7 meters
- Powder coated grey raal 7035
- Bunded 270 litre base fuel tank complete with 3 way valve
- Central lift point and forklift pockets complete with rubber bumpers
- 4 pole circuit breaker with earth leakage protection
- Hardwire via copper bus bars
- Micro switch protection mounted under perspex
- CT for genset paralleling
- Racor filter
- Deep sea 8610 loadshare control panel
- Plastic coated locks/handles
- Lockable canopy with single common key
- IVECO water separator filter
- Sump oil vac pump
- Battery isolator
- Socket kit – 1 x 125amp 3 phase
- Oil pressure & water temperature sensor
- Motorised MCCB
- Velcb with on/off switch
- External contact for autostart

Standby (kVA)	Prime Power (kVA)	Engine Make Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
220	200	IVECO/ CUMMINS	Electronic	270 Bunded	21.55	32.33	43.10	68	L - 3380 H - 1850 W - 1130	2690	Deep Sea 8610 Loadshare

South East Depot

Europa Park,
London Road,
Grays, Essex,
RM20 4DB
T: 01375 366766

Midlands Depot

Fairfield Park,
Off Fairfield Road,
Halesowen,
West Midlands
B62 9JL
T: 0121 559 1818

South West Depot

Bradley Road,
Bristol
BS20 7NZ
T: 0117 901 2199

Scotland Depot

Nasmyth Square
Livingston
West Lothian
EH54 5GG
T: 01506 353 399

North East Depot

Portobello Trading
Estate
Shadon Way
Chester-Le-Street
DH3 2RN
Tel: 0191 411 1200

power@johnfhunt.co.uk

johnfhuntpower.co.uk

2022

